



**Contacts - Solid**

Size	Part No.		Plating	Wire Size		Recommended Strip Length - mm	Max. Rated Amps @ 125° Continuous
	Pin	Socket		AWG	mm <sup>2</sup>		
20	<b>0460-202-2031</b>	<b>0462-201-2031</b>	Gold	20	0.2 - 0.5	4.0 - 5.5	7.5
	<b>0460-202-20141</b>	<b>0462-201-20141</b>	Nickel				
16	<b>0460-202-1631</b>	<b>0462-201-1631</b>	Gold	16 - 20	0.5 - 1.0	6.4 - 8.0	13
	<b>0460-202-16141</b>	<b>0462-201-16141</b>	Nickel				
16 Green Band	<b>0460-215-1631</b>	<b>0462-209-1631</b>	Gold	14	1.0 - 2.0	6.4 - 8.0	13
	<b>0460-215-16141</b>	<b>0462-209-16141</b>	Nickel				
12	<b>0460-220-1231</b>	<b>0462-210-1231</b>	Gold	12 - 14	2.0 - 3.0	5.6 - 7.2	25
	<b>0460-204-12141</b>	<b>0462-203-12141</b>	Nickel				
8	<b>0460-204-08141</b>	<b>0462-203-08141</b>	Nickel	8 - 10	5.0 - 8.0	11.0 - 12.5	60
4	<b>0460-204-0490</b>	<b>0462-203-04141</b>	Nickel	6	13.0	11.0 - 12.5	100



**DEUTSCH**

CAGE Code Z1N72

Cambridge Technologies • No 17, 85-91 Keilor Park Drive • Tullamarine, Victoria 3043  
Phone +61 3 8336 1000